

# WHEEL LOADER SNOWBLOWERS



HDS9200



HDS7100



HDS7101



## BLOWER PACKAGES AVAILABLE FOR SMALL & COMPACT LOADERS!

### Standard Features:

- **100% Hydraulically Powered:** Low cost of operation and minimal wear on parts
- **No Gear Box or Shear Pins:** Abrupt stops will trigger oil to bypass protecting the blower
- **Rotary Spout:** 270° rotation can be turned with a small finger movement
- **Spout Deflector:** Hydraulically powered for precise control and accurate placement
- **Digital Display:** Mount in the cab to monitor blower performance (HDS7100 Option)
- **Small Control Module:** Smoothly manipulate all hydraulic functions with ease (HDS7100 Option)
- **Quick-Tach:** Multiple options to match various wheel loader configurations
- **Skid Shoes:** Steel shoes are adjustable, replaceable and will protect the unit from excessive wear
- **Side Skid Plates:** Replaceable curb skids to protect unit from excessive wear
- **Tiger Teeth:** Innovative design chews up hard packed snow and ice
- **Grader Blade:** Made from American steel, bolts on quickly and replaceable for ultimate machine protection
- **Robust Powder Coated Paint:** Shot blasted bare metal, then coated and baked in excess of 400° for toughest finish available
- **Continually Improving:** HitchDoc is engineering these blowers to fit more wheel loader brands and models



I-90 & US 71 | Jackson, MN

800.446.8222 | 507.847.4049 | Fax 507.847.5100

Sales@HitchDoc.com | ISO 9001 & 14001

[WWW.HITCHDOC.COM](http://WWW.HITCHDOC.COM)



# WHEEL LOADER SNOWBLOWERS



	Cut Width	Cut Height	Overall Width	Overall Height	Weight	Auger	Chute Discharge Height	Hydraulic Requirements
<b>HDS 9200</b>	108"	45"	114"	127"	5,200 lbs.	Dual, 16"	105-150"	35-50 GPM at 3700+ psi

## Specifications:

- **Loader Needs:** Third hydraulic valve with 35, 40, or 50 gpm at 3,700+ psi & **hydrostatic transmission** with creeper capability
- **Side Discharge:** Efficiently throws snow to the right or left without using the spout
- **Telescoping Truck Loading Spout:** Reach the highest of trucks seamlessly
- **Enclosed Auger Chain:** #80 Heavy Duty chain & spring tensioned idler sprocket
- **Heavy Duty Double Auger:** Includes 16" flighting & rugged 1 1/2" grease-able bearings



	Cut Width	Cut Height	Overall Width	Overall Height	Weight	Auger	Chute Discharge Height	Hydraulic Requirements
<b>HDS 7100</b>	84.5"	36.5"	90.5"	73.7"	1,480 lbs.	Single, 20"	68"	25-40 GPM at 2,800-4,000 psi
<b>HDS 7101</b>	96.7"	36.5"	96.7"	73.7"	1,557 lbs.	Single, 20"	68"	25-40 GPM at 2,800-4,000 psi

## Specifications:

- **Loader Needs:** Third hydraulic valve with 25-40 gpm at 2,800-4,000 psi & **hydrostatic transmission** with creeper capability
- **Versatile Mounting:** Attach with ease to high flow skid steers, wheel loaders with JRB, Fusion, or ISO connections
- **Performance Packages:** Select the ideal valve package & control option for high performance operation season after season
- **Telescoping Truck Loading Spout:** Load trucks with ease and increase the versatility of your blower

For more information, contact your local dealer or [Sales@HitchDoc.com](mailto:Sales@HitchDoc.com)